

STARMAX



GOLF / UTILITY VEHICLES

MOTIVE DEEP CYCLE AGM

BATTERIES

SDC8-165-GC8 (8Volts)




www.starmaxbatteries.com

SDC SERIES - SUPERIOR CYCLING NON SPILLABLE

8V 165Ah



LAYOUT



General Features

- ✓ **Stable initial capacity**
 - PAM/NAM amount optimization
 - 4BS crystal paste mixing & curing technology
 - Double layer separator technology
 - Improved design electrolyte S.G.
- ✓ **Excellent deep cycle performance**
 - Plate assembly pressure re-engineering
 - New PAM/NAM recipe introduced
 - Gel electrolyte technology
 - Rare earth alloy
 - Double layer separator technology
 - Lower acid filling temperature
- ✓ **Solve NAM sulphation**
 - Carbon boost technology
 - Pre-sulfate technology

- ✓ **Improved PSoC cycling**
 - Carbon boost technology
 - Mix carbon boost technology
 - Targeting for higher level through carbon technology
- ✓ **Less water loss**
 - PAM/NAM amount optimization
 - New PAM/NAM recipe introduced
 - Rare earth alloy
- ✓ **Delay PAM softening and shedding**
 - Plate assembly pressure re-engineering
 - 4BS crystal paste mixing & curing technology
 - Higher paste density
- ✓ **Optimize electrolyte stratification**
 - Introduce AGM-GEL technology




SPECIFICATIONS

Voltage	8V	
Dimension	Length	260mm(10.2 inches)
	Width	180mm(7.09 inches)
	Container height	252mm(9.92 inches)
	Total Height	274mm (10.8 inches)
Approx Weight	29.274kg (64.5) lbs	
Terminal	DT (5/16")	
Container Material	ABs	
Reserve Capacity	25A	325 min
	56A	130 min
Capacity	20HR	165Ah
	10HR	155Ah
	5HR	140Ah
Operating Temp. Range	Discharge	-25~55°C (-4~131°F)
	Charge	0~40°C (32~104°F)
	Storage	-15~40°C (5~104°F)


Applications

- ✓ Arial Work Platforms
- ✓ Golf cart & Utility Vehicles
- ✓ Transportation
- ✓ Floor Cleaning Machines
- ✓ Marine & Recreation Vehicles
- ✓ Solar & Renewable Energy

Charging Profiles




Cycle Life in Relation to Depth Of Discharges




Relationship of OCV and State of Charge

(25°C, 77°F)



Self Discharge Characteristics



No supplementary charge required (Carry out supplementary charge before use if 100% capacity is required)

Supplementary charge required before use to recover full capacity

Supplementary charge may often fail to recover the capacity. The battery should never be left standing till this is reached

The max Storage time should not be above 15 months



Starmax Corporation

1585 Cliveden Avenue, Delta, British Columbia
V3M 6M1, Canada

Phone: +1 888 669 1310

Email: info@starmaxbatteries.com

Website: www.starmaxbatteries.com

